Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S1890 F
	Date of issue	30.12.2014

Company	TVP Solar SA	**Country**		Switzerland
Brand (optional)		**Website**		www.tvpsolar.com
Street, number	36, Place du Bourg-de-Four	**E-mail**		info@tvpsolar.com
Postal Code	1204	**Tel.**	+41	22 5349087
City	Geneva	**Fax**	+41	22 3106180

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
Integration in the roof possible ?	No

Collector name	Aperture area (Aa)	Gross length	Gross width	Gross height	Gross area (AG)	Power output per collector unit G = 1000 W/m² Tm-Ta : 0 K	10 K	30 K	50 K	70 K
	[m²]	[mm]	[mm]	[mm]	[m²]	[W]	[W]	[W]	[W]	[W]
MT-Power v3.11	1.05	1 692	692	62	1.17	797	791	774	752	724

Collector efficiency parameters related to aperture area (Aa) Type of fluid and flow rate see note 1	η_{0a}	0.759	-
	a_{1a}	0.508	W/(m²K)
	a_{2a}	0.007	W/(m²K²)
Stagnation temperature - Weather conditions see note 2	t_{stg}	329	°C
Effective thermal capacity	$c_{eff} = C/A_a$	7.51	kJ/(m²K)
Max. operation pressure - see note 3	p_{max}	1500	kPa

Incidence angle modifiers $K_\theta(\theta)$	G_{DIF}/G_{TOT} min	G_{DIF}/G_{TOT} max	θ_T / θ_L	50°	*10°*	*20°*	*30°*	*40°*	*60°*	*70°*
	min	max	$K_\theta(\theta_T)$	0.91	1.00	0.99	0.98	0.95	0.84	0.70
	-	-	$K_\theta(\theta_L)$	0.91	1.00	0.99	0.98	0.95	0.84	0.70

G_{DIF}/G_{TOT}: min&max - while measuring — ***Optional values***

Testing Laboratory	TZS, ITW University of Stuttgart
Website	www.tzs.uni-stuttgart.de
Test report id. number	11COL1028
Date of test report	30.12.2014
Perf. test method	EN 12975-2 6.3 (outdoor)

Comments of testing laboratory :

none

Note 1	**Fluid**	Water	**Flow rate**	0.020	kg/s per m²
Note 2	**Irradiance, Gs=1000 W/m²** **Ambient temperature , Ta=30 °C**				
Note 3	**Given by manufacturer**				

TZS Forschungs- und Testzentrum für Solaranlagen
Institut für Thermodynamik und Wärmetechnik
Universität Stuttgart
Pfaffenwaldring 6, 70550 Stuttgart (Vaihingen)

VERSION 3.6, 2012.01.13

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S1890 F
	Issued	30.12.2014

Annual collector output kWh

Collector name	Location and collector temperature (Tm)														
	Athens			Davos			Stockholm			Würzburg					
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C			
MT-Power v3.11	1 288	1 208	1 100	1 209	1 117	1 002	820	741	651	876	795	699			

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: http://www.estif.org/solarkeymark/annexb1.php)

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

Datasheet version:
VERSION 3.6, 2012.01.13
Calculation program version:
3.07, October 2011 (SP)